

Co. Reg. No. 199103406Z



CF 503

SOLVENT CLEANER

DESCRIPTION

CF 503 is a blended solvent cleaner designed to remove tar, type mark, vanish, glue, grease and oil from most metal surfaces and floors. Silk fabric can be cleaned by brushing without risk of shrinking.

APPLICATION

CF 503 is used with high degree of efficiency and operating safety over a wide range of applications. It can be used to remove harden tar, varnish on ceramic flooring by wiping with a dry cloth. Sticker glue could be easily remove by wiping with dry cloth. Grease and oil on metal surfaces can be easily clean by wiping with cloth or hand-towel.

FEATURES

- Non-flammable
- No flash point
- Optimum soil removal rate
- Streak free on metal surfaces
- Specific gravity @ 20°C : 1.605-1.609
- PH – 5.5

METHOD OF USE

CF 503 is used concentrated by wiping, brushing, dipping and spray application, mechanical agitated tanks will reduce cleaning time. Apply direct from drum on soil surface by brushing and wiping, no rinsing is required in this circumstance. CF 503 is safe on all metals but can damage some paint and plastics. Always test such surfaces first.

SAFETY

Avoid prolong contact with skin and eyes. Avoid breathing vapors of this product. It should not contact with low density plastic materials.

PACKING

5 litres and 25 litres

Important Notes

Chemforce product data sheets are regularly reviewed and available on request. The successful use of this product is dependent on a number of factors. As the information contained in this literature can only be of a general nature, it is advisable to consult our technical department if there is any doubt about the correct use of this product in a particular application. Our Sales and Technical representatives are available to provide further technical and commercial assistance.

CHEMFORCE PTE LTD

2B Sungei Kadut Drive,
Singapore 729555.
Tel: +65 6365 2833 Fax: +65 6365 2700
Email: sales@chemforce.com.sg
Website: www.chemforce.com.sg