Co. Reg. No. 199103406Z



# **CHEMPOL**

# **HIGH GLOSS FLOOR FINISH**

#### DESCRIPTION

CHEMPOL is a high quality floor finish manufactured in USA that performs excellently under conventional or ultra-high speed maintenance program.

### **APPLICATION**

CHEMPOL can be used on all types of thermoplastic and synthetic floor coverings. It is also suitable for types of stone floors including marble, tiles and terrazzo. Certain stone flooring may require the use of an undercoat of sealer for better adhesion. The high gloss can be further enhanced by being thermally activated by buffing with a speed machine.

### **FEATURES**

- Slip-resistant and non-yellowing
- Protects surface and ease cleaning
- Prevent absorption of dirt and stains
- High gloss with easy application
- Not suitable for unsealed wood or cork floorings
- Covers an average of 2,500 square feet per liter for 1 coat

## **METHOD OF USE**

- Before application, ensure that the surface is thoroughly clean and dry.
- For floors that requires stripping, use floor machine with CHEM STRIP to ensure that all
  previous coatings of wax are removed thoroughly.
- Apply a thin coating of CHEMPOL using a clean mop or a wax applicator evenly over the entire surface.
- Allow to dry completely for about 30 minutes before applying the next coat. Three to four coats is recommended if the floor has been stripped.
- Allow sufficient drying time before allowing traffic on the floor.

#### **PACKING**

5 US Gallons

#### Important Notes

Chemforce product data sheets are regularly reviewed and available on request. The successful use of this product is dependent on a number of factors. As the information contained in this literature can only be of a general nature, it is advisable to consult our technical department if there is any doubt about the correct use of this product in a particular application. Our Sales and Technical representatives are available to provide further technical and commercial assistance.

#### **CHEMFORCE PTE LTD**

2B Sungei Kadut Drive, Singapore 729555. Tel: +65 6365 2833 Fax: +65 6365 2700 Email: sales@chemforce.com.sg

Website: www.chemforce.com.sq